

COLODUR

MONO-COMPONENT ALIPHATIC POLYURETHANE RESIN

Mono-component polyurethane waterproofing resin, specil for surfaces

APPLICATIONS

- Sealing and finish on stamped concrete floors
- Sealing of decorative paving with coloured aggregates
- Finish, protection and wearing course on epoxy pavements
- Finish, protection and wearing course in waterproofing done by IMPERLUX POL
- Surface protection
- Waterproofing of old supports, which will not suffer dilation



Waterproofing



QUALITY AND ENVIROMENT
CERTIFIED COMPANY

COLODUR

MONO-COMPONENT ALIPHATIC POLYURETHANE RESIN



QUALITY AND ENVIRONMENT
CERTIFIED COMPANY

PRODUCT DATASHEET

Finish	Shiny smooth
Viscosity	ca 100 (20°C, mPa)
Dry to touch without being sticky	24 hours
Complete drying at 25°....2 days	Complete drying at 15°C.....7days
Thinner	Xylene
Passable	After 24 hours

PROPERTIES AND ADVANTAJES

- Easy application
- Repaintable in subsequent repairs
- Resistant to a wide range of chemical agents, great behavior to oils and fuels
- Pavements without joints
- Decorative finishes
- Great mechanical properties
- Waterproof coating
- Clean pavement and easy maintenance

INSTRUCTIONS FOR USE

- 1.- The surface must be completely clean.
- 2.- The moisture on the support must be less than 4%. On new pavements, it is advisable, not to paint before a month.
- 3.- If the support has no pores, we will apply mechanical means (sanding – sucked or filed) or chemical means (LIMPIAFIX)
- 4.- The first coat could be applied 5 or 10% thinned, with DIPOL polyurethane thinner.
- 5.- To get a good adherence, leave it no more than 24 hours.
- 6.- It is advisable to apply the performance of the paint, on the maximum layers possible.
- 7.- If you desire a nonslip support, to sprinkle dust of nonslip powder on it, remove the excess after 24 hours and apply another coat



Paint brush



Paint roller

PRESENTACIÓN

COLODUR is presented in hermetic containers, following the EU rules for packing and chemical products warehousing. To store at temperatures between 5° and 30°. Duration of the product in its original packaging; 8 months. Do not apply at extreme temperatures, below 0°C and above 35°C

PRECAUTIONS

- R10:** Inflammable
- R36/37:** Irritating to eyes and respiratory system
- S20/S21:** When using, do not eat, drink or smoke
- S22:** Dust not to be inhaled
- S36/37:** Wear suitable protective clothing and gloves
- S26:** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
- S46:** in case of swallowing, seek medical advice. Show the packaging or the label
- S51:** Use only, in well-ventilated areas

OUTPUT

The output will be between 1 and 1.5 kg/m², depending on the roughness of the support. It is advisable to give 3 coats

. This product datasheet, as well as the other technical information, are used, only for the product description, instructions for use and its applications. The information given is based on our own knowledges, obtained from the practice, bibliography, and laboratory essays. The consumption and specifications from this datasheet, are based on our own experience, so, it could suffer variations due to the different work conditions. The consume and real dosifications must be determined on the work.

We do not have responsibility in other product applications which have not been specified. This datasheet lost its value if it appears a new edition. You must consult with our technical department if you have any doubt not explained on this datasheet. We guarantee our products in case that any of them suffer from a defect of quality, being our responsibility to refund the value of the delivered goods.